

SENSORS

Compact range of Sun, Star, Horizon, and Magnetometers



NEW PRODUCT PARTNERSHIP

Introducing the Auriga Processing Unit

We are delighted to announce the product partnership between CubeSpace and Sodern!

Sodern's Auriga™ star tracker, known for its compact design and suitability for small satellite constellations, brings heritage of over 50 years and more than 1,500 units successfully operating in orbit.

With the in-house development of the Auriga processing unit, customers can seamlessly integrate the Auriga™ star tracker directly with our Turn-Key ADCS. This makes it an ideal choice for missions that demand high pointing accuracy, wider maneuvering capabilities, and exceptional performance throughout the orbit.

Auriga™ – Star Tracker



Auriga Processing Unit





	FINE SUN SENSOR	EARTH HORIZON SENSOR	STAR TRACKER*
PERFORMANCE			
Accuracy [°]	0.2° (vector) 2σ	1° (roll and elevation) 3σ	35" (cross-axis) 175" (roll) 3σ
Max slew rate [°/s]	70	14	0.3
PHYSICAL			
Mass [g]	15	18	70
Dimensions [mm]	35x24x22	35x24x20	43x24x63.75
Detection field of view [°] (Horizontal/vertical)	166	90/80	NA
Detection field of view [°] (Diagonal)	176	90	NA
Total Sun and Earth Exclusion Angle [°]	NA	NA	70
POWER AND DATA			
Data bus	CAN/UART/I2C/RS-485		CAN/UART/RS-485
Connector	Molex Micro-Lock Plus		
Update rate [Hz]	Up to 2	Up to 2	Up to 1
Supply voltage [V]	3.3	3.3	3.3
Peak power [mW]	200	152	363
Average power [mW]	93	126	192

*Preliminary Specifications

	DEPLOYABLE MAGNETOMETER	COMPACT MAGNETOMETER
PERFORMANCE		
Noise per channel [3-sigma] [nT]	50	120
Linearity Error (Full Scale) [%]	0.6%	0.6%
Sensitivity [nT]	13	25
Field Measurement Range [G]	±8	±8
PHYSICAL		
Mass [g]	16	6
Dimensions [mm] *Height with protrusion is 9.6	17x82x6.5*	24x24x7.8
POWER AND DATA		
Data bus	CAN/UART/RS-485	CAN/UART/I2C/RS-485
Connector	Molex Micro-Lock Plus	
Update rate [Hz]	5	6
Supply voltage [V]	3.3	3.4
Peak power [mW]	230	230
Average power [mW]	50	50
Deployment power [mW]	2 350	N/A

AURIGA PROCESSING UNIT

PHYSICAL	
Mass [g]	55.5
Dimensions [mm]	74.3 x 52.5 x 14.05
POWER & DATA	
Data bus	CAN/UART/RS-485
Connector	Molex Micro-Lock Plus
Update rate [Hz]	5
Supply voltage [V]	3.3 and 5.0
Peak power [mW]	347 / 396 [1 OH / 2 OH]
Average power [mW]	326 / 381 [1 OH / 2 OH]

QUALIFICATION TEST	
Radiation (TID)	24 kRad
Vibration	14 g RMS (NASA GEVS)
Shock	1500 g
Thermal (Vacuum) [°C]	-20 to 80 °C
Thermal (Hot & Cold Start) [°C]	-35 to 70 °C

